

RoHS

# SK78XX-2000(L) Series

## WIDE INPUT NON-ISOLATED & REGULATED SINGLE OUTPUT

### FEATURES

- Efficiency up to 92%, No heatsink required
- 2A large current output
- Operating temperature : -40°C ~ +85°C
- Short circuit protection, thermal shutdown
- Low ripple and noise
- Micro miniature SIP package, meet UL94-V0 requirement
- Ultra low power loss
- Negative output application
- Industry standard pinout
- Pin-out compatible with LM78XX Linear
- MTBE>2000,000Hours

### PRODUCT PROGRAM

Part Number	Input Voltage(VDC)		Output		Efficiency (%) (Typ.)	
	Nominal	Range	Voltage (VDC)	Current (mA)	Vin (min.)	Vin (max.)
SK7801-2000(L)	12	4.75-18	1.5	2000	79	76
	12	4.75-16	-1.5	-1300	74	78
SK78X2-2000(L)	12	4.75-18	1.8	2000	81	79
	12	4.75-16	-1.8	-1300	75	80
SK7802-2000(L)	12	4.75-18	2.5	2000	85	83
	12	6.5-15	-2.5	-1200	81	84
SK7803-2000(L)	12	4.75-18	3.3	2000	87	86
	12	6.5-16	-3.3	-1200	82	86
SK7805-2000(L)	12	7-18	5	2000	91	88
	12	7-13	-5	-1000	84	88
SK78X6-2000(L)	12	8.5-18	6.5	2000	92	91
	12	7-13	-6.5	-800	87	90

Add suffix "L" for 90° bend pins, for example: SK78 05-2000L.

### APPLICATIONS

Upgraded SK78XX-2000(L) series switching regulators are ideal replacement for SK78XX linear regulators and LDOs. The efficiency of up to 92% means that very little energy is wasted as heat so there is no need for any heat sinks with their additional space and mounting costs. They are widely used in industrial control, instrumentation, and electric power applications.


### OUTPUT SPECIFICATIONS

Item	Test conditions	Min.	Typ.	Max.	Units
Output voltage accuracy	100% full load, input voltage range		±2	±3	%
Line regulation	Vin=min. to max, at full load		±0.5	±0.75	
Load regulation	10% to 100% load		±0.5	±1.0	
Ripple & Noise*	20MHz bandwidth (refer to figure 7)		25	45	mVp-p
Short circuit input power			0.5	1.8	W
Short circuit protection		Continuous, auto-recovery			
Thermal shutdown	Internal IC junction		150		°C
Output current limit			5000		mA
Switching frequency	Full load, input voltage range	300	340	380	KHz
Quiescent current	Positive output		5	10	mA
	Negative output		11	13	
Temperature coefficient	-40°C ~ +85°C ambient			±0.03	%/°C
Max capacitance load	Positive output			1000	µF
	Negative output			470	

\*Test ripple and noise by "parallel cable" method.

### MODEL SELECTION

SK7805-2000



### SCHMID-MULTITECH GMBH


Address: Weinbergstraße 60b,  
93105 Tegernheim, Germany  
Tel: +49-9403-9510-0  
Fax: +49-9403-9510-22  
[Http://www.schmid-m.com](http://www.schmid-m.com)

### COMMON SPECIFICATIONS

Operating temp. range	-40~+85 □	
Operating case temp.	+100 □ (max)	
Storage temp. range	-55~+125 □	
Cooling	Free air convection	
Lead temperature**	300 □ (max)	
Storage humidity range	≤ 95%	
Case material	Plastic(UL94-V0)	
MTBF	> 2000kHours	
Package weight	4.0g	
Conducted emissions (Refer to Figure6)	EN55022	CLASS B
Radiated emissions	EN55022	CLASS B
ESD	EN61000-4-2	CLASS A


\*\*1.5mm from case for 10 seconds

## TYPICAL CHARECTERISTICS



(figure 1)

## TYPICAL APPLICATION CIRCUIT




(figure 2)

## EXTERNAL CAPACITOR TABLE

Part Number	C1 (Ceramic capacitor)	C2 (Ceramic capacitor)
SK7801-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/6.3V
SK78X2-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/6.3V
SK7802-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/6.3V
SK7803-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/6.3V
SK7805-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/16V
SK78X6-2000(L)	10 $\mu$ F/25V	22 $\mu$ F/16V

## APPLICATION EXAMPLE




(figure 3)

Note:


1. C1 and C2 are required and should be fitted close to the converter pins.
2. The capacitance of C1 and C2 sees external capacitor table, it can be increased properly if required, and tantalum or low ESR electrolytic capacitors may also suffice.
3. No parallel connection or plug and play.

## INPUT FILTER CIRCUIT CONNECT




(figure 4)

## OUTPUT FILTER CIRCUIT CONNECT



(figure 5)


## EMC RECOMMENDED CIRCUIT



(figure 6)


## TEST CONFIGURATIONS (TA=25°C)

### 1 Efficiency and Output Voltage Ripple Test



(figure 7)

### 2 Start-up and Load Transient Response Test







(figure 8)

## CHARACTERISTICS CURVE

### Efficiency



### Ripple



# OUTLINE DIMENSIONS & FOOTPRINT DETAILS



## MECHANICAL DIMENSIONS

### SK78XX-2000



Note:  
Unit:mm[inch]  
Pin section tolerances:±0.10mm[±0.004inch]  
General tolerances:±0.25mm[±0.010inch]


### SK78XX-200L




Note:  
Unit:mm[inch]  
Pin section tolerances:±0.10mm[±0.004inch]  
General tolerances:±0.25mm[±0.010inch]

## RECOMMENDED FOOTPRINT

### SK78XX-2000



### SK78XX-200L




Note:  
grid:2.54\*2.54mm.


FOOTPRINT DETAILS		
Pin	Positive	Negative
1	+Vin	+Vin
2	GND	-Vout
3	+Vout	GND

## TUBE OUTLINE DIMENSIONS

### SK78XX-2000



### SK78XX-200L



Note:  
Unit:mm[inch]  
General tolerances:±0.50mm[±0.020inch]  
L=530mm[20.866inch] Devices per tube quantity: 44pcs  
L=220mm[8.661inch] Devices per tube quantity: 17pcs  
Short tube inner packaging dimensions: L\*W\*H=255\*170\*80mm  
Short tube outer packaging dimensions(with six inner packaging boxes):  
L\*W\*H=375\*280\*270mm  
Long tube inner packaging dimensions: L\*W\*H=580\*200\*100mm  
Long tube outer packaging dimensions(with two inner packaging boxes):  
L\*W\*H=600\*215\*220mm  
Long tube outer packaging dimensions(with three inner packaging boxes):  
L\*W\*H=600\*215\*325mm

## Note:

- All specifications measured at Ta=25°C, humidity <75%, nominal input voltage and rated output load unless otherwise specified.
- Only typical models listed, other models may be different, please contact our technical person for more details.
- In this datasheet, all the test methods of indications are based on corporate standards.